



Kytex Solutions, Inc.
Research • Development • Manufacturer

Equip-Coat SE

EQUIP-COAT SE is all natural Soy based liquid compound that prevents bonding of concrete to trucks and equipment.

EQUIP-COAT SE reacts with the alkalinity of the cement and forms a barrier between the metal surface and the concrete, therefore any built up can easily be removed with water.

This product will not interfere with the setting of cement. It is easy and safe to use. It does not contain any form oil or silicone.

Advantages:

- All natural Soy based
- No VOC
- Biodegradable
- No Solvent

PROPERTIES:

Appearance & Odor:	Amber colored solution with mild odor
Solubility in Water:	Emulsifiable

APPLICATION METHOD:

1. Hose down the concrete and mortar residue from mixers, pavers hoist buckets, power trowels, truck pans, wheel barrows, chutes, conveyors and other equipment with water at the end of the work period.
2. Dilute the product with up to 30 parts of water depending the plant conditions and mix well before applying.
3. Spray EQUIP-COAT SE to the dry surface. Regular application of EQUIP-COAT will help keep trucks and equipment completely free of concrete deposits and rust. The coat will dry in 10-15 minutes and be ready for use.
4. After few applications the product will built -up on the equipment surfaces and therefore less product can be used as the time goes by.

OTHER APPLICATIONS:

Aluminum windows, frames, glass, floors and other parts and areas subject to spattering with cement or plaster can be pre-coated with EQUIP-COAT. Subsequent spattering can be removed easily and cleanly.