



Technical Data Report

STRIP-EZE

HEAVY DUTY CLEANER

DESCRIPTION

STRIP-EZE is a USDA authorized strong cleaner in a gel base for quick effective removal of soil and wax on floors, baseboards, and wall tiles. Thick gel formula stays where sprayed and the white foam shows where applied, eliminating running and guesswork. Upside-down valve allows easy application. Can sprays upside-down only.

APPLICATIONS

STRIP-EZE is excellent for use in industrial plants, hotels/motels, warehouses, hospitals, schools, offices and institutions. Cleans baseboards, wall tiles and floors. NOTE: Painted surfaces should be tested prior to general use.

FEATURES & BENEFITS

- Clinging formula remains on vertical surfaces until rinsed or wiped away.
- Can spray upside down for ease of application.
- Quick penetration and dissolution of polymers
- Pleasant fragrance

SPECIFICATIONS

FORM: Water Base Aerosol Foam
ODOR: Soapy
COLOR: White
DETERGENCY: Excellent
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 year +
COLD STABILITY: 32° F
PHOSPHATES: None

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 100%
SPECIFIC GRAVITY: 1.0
% VOLATILE BY VOLUME: 98%
pH: 9.5
PROPELLENT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: No

LABEL INFORMATION

STRIP-EZE HEAVY DUTY CLEANER

This product is designed to clean soil and wax build-up from baseboards, ceramic wall tile and similar areas. The thick gel formulation stays in place on vertical surfaces for easy cleaning. Foaming action allows easy identification of areas already treated. Sprays upside-down for easy, quick operation. Cleans and removes wax and soil in one simple operation.

DIRECTIONS FOR USE

Prior to use, test the surface in an inconspicuous area to check for discoloring or possible damage to surface.


Shake well. Remove protective cap. Holding can upside-down, point opening in spray tip toward surface. Keep can six inches from the surface. Press tab on the tip down to spray. Apply a thin coat. Spray to cover all soil and wax build-up on the surface.

Do not apply to painted surfaces. Wipe off any overspray immediately. Wait at least 3 to 5 minutes for heavily soiled areas. Scrub with a wet sponge or cleaning pad to remove soil and wax build-up. Rinse with clean warm water.

CAUTION: Contents under pressure. Do not expose to heat or flame. Do not puncture or incinerate container. Exposure to temperatures above 120° F may cause bursting. This product may cause eye irritation. If material gets in eyes, flush thoroughly with water. If irritation persists, see physician. Wash hands thoroughly after handling.

CONTAINS (CAS#): Water (7732-18-5), 2-Butoxy Ethanol (111-76-2), Propane/n-Butane (68476-86-8), Nonionic Surfactant (127087-87-0)

HEALTH	2
FLAMMABILITY	0
REACTIVITY	1
PERSONAL	B



PACKAGING INFORMATION

12 - 20 oz cans per case 18 oz net weight