

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 249
IDENTITY: BRILLIANCE

Revision Date: 01/24/2007

Section I

Manufacturer's Name: QUEST CHEMICAL CORPORATION
Address: 12255 FM 529
NORTHWOODS INDUSTRIAL PARK
HOUSTON
State: TX Zip Code: 77041

Telephone Numbers:
Emergency: 800/255-3924
Information: 713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 2 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
ISOPARAFINIC HYDROCARBON	64742-47-8	400 PPM	400 PPM		_____
MINERAL SEAL OIL	64741-44-2	5 MG/M3	5 MG/M3	N/A	_____
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	430	Specific Gravity (water=1)	0.81
Vapor Pressure(mm Hg)	<0.1	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	.2
Solubility in Water:	0%	(Butyl Acetate=1)	

Appearance and Odor: CLEAR SPRAY/LEMON SCENT

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used):>185F TCC Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS WHEN INDICATED

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 249

Stability: Unstable: Conditions to avoid: TEMPERATURES ABOVE 120 F
Stable: X HOT SURFACES
Incompatibility (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY LEAD TO UNCONSCIOUSNESS.
EYES: IRRITATION, REDDENING. SKIN: MAY CAUSE LOCALIZED DRYNESS IF OVER-
EXPOSED.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. SKIN:
IN CASE OF CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. EYES: FLUSH WITH
WATER FOR 15 MINUTES. CONTACT PHYSICIAN IF IRRITATION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG
OR USE SOME ABSORBENT CLAY MATERIAL. DISPOSE OF RESIDUE IN ACCORDANCE WITH
FEDERAL, STATE AND LOCAL GUIDELINES.

Waste Disposal Method: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT
REUSE CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR
HEAT OR OPEN FLAMES. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE
BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: N/A
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER USE