



## **FOAMAWAY**

### **DESCRIPTION**

When using many cleaning products, such as detergents, a considerable amount of foam is created. This causes recovery tanks to fill up rapidly and often results in overflowing suds. This overflow often carries soiled water with it, thus soiling and soaking anything around the recovery tank. This product is a liquid silicone emulsion formula for use in the recovery tanks of water extraction cleaning equipment and other equipment utilizing recovery tanks. This product may be used as a general purpose defoamer while cleaning rugs and carpets.

### **INSTRUCTIONS**

Shake well before using. Pour 1-2 ounces of this product into vacuum hoses or you may pour it directly into the solution recovery tank prior to foaming or even after foaming begins. May also be used in a truck mounted system. Its always easier to prevent foam before you start than it is to remove it after it has become a problem. If in doubt as to whether this product is needed, it is always better to use a little beforehand.

If this product is exposed to extreme temperature changes it may separate in the container, so for best results please shake well before using. If separation does occur, shaking well will place product back into solution with no damage to active ingredients.

This product works well in portable self contained or truckmounted equipment. Once applied to vacuum hose or pickup tank it may take a few minutes for the foam level to drop.

### **FEATURES**

- Excellent for industrial
- Contains corrosion inhibitors
- Silicon based

### **SPECIFICATIONS**

Appearance:	White Turbid Liquid	pH:	7.8
Odor:	Bland	Detergency:	None
Specific gravity:	.01		

### **SAFETY**

Keep this and all chemicals out of the reach of children! Caution: Product may be harmful if swallowed. Contact physician immediately. For skin or eye contact, flush with clear water for 15 minutes. For eye contact, consult physician immediately.