



EXECUTIVE

DESCRIPTION

A modern combination of acrylic copolymers metal cross-linked to resist detergents and the scuffing of floors. It is fast laying, quick drying, and its initial gloss is excellent for use in schools, hospitals, or other high traffic areas where high or low speed buffing without powdering is desired. Synthetic detergents and emulsifiers have little effect on this product's gloss and durability. Surfaces coated with this finish will shine even after repeated abuse.

INSTRUCTIONS

For best results apply full strength over freshly stripped and rinsed floor. Apply first coat lightly, being more concerned with even coverage than quantity of finish applied. Allow approximately 15 to 20 minutes drying time between coats then apply a second coat a little heavier than the first. Repeat this procedure for up to 7 coats if necessary or desired. Please allow 24 hours cure time after last coat before high speed burnishing with a pad any darker than beige although under some conditions burnishing between coats can be performed if proper care is taken to test prior to doing.

FEATURES

- Outstanding Gloss
- Rapid Recoatability
- Excellent Buff Response
- Low Mop Drag
- Fast Dry
- Good Durability

SPECIFICATIONS

Appearance: White Emulsion
Solids: 20%
Specific gravity: 8.50 lbs. per gallon

pH: 8 - 9
Biodegradable: Yes
Durability: Excellent

SAFETY

Keep this and all chemicals out of the reach of children! This product is non-toxic to users, and non-corrosive to metal at any dilution. It is non-flammable and has no flash point.