



GRAFFITI PROTECT SR

DESCRIPTION

Graffiti protect is designed to be a clear, long lasting penetrating graffiti protection and sealer for use on variety of surfaces including: concrete, brick, stucco, block and tile.

Graffiti protect fills voids in porous surfaces and minimizes the graffiti penetration, thus allowing for the graffiti removal with an approved cleaner and low-pressure water spray.

INSTRUCTIONS

1. Apply the product by low pressure spray unit, brush or roller
2. Spray to saturation level with minimum of 5 inches of rundown.
3. Do not apply when inclement weather is imminent
4. Protect glass, painted surface. Immediately wash off any material on non-treated surfaces with mineral spirits. Tools can be cleaned with mineral spirits.

Coverage:

Concrete	100-150 square feet per gallon
Brick	125-150 square feet per gallon
Block	125-150 square feet per gallon

FEATURES

- Dries to clear non-yellowing film (resistant to ultraviolet rays)
- Flexible after curing, allowing for structural movement
- Breathable, allowing moisture to escape from substrate
- Resistant to salts and chemicals
- Excellent water repellent characteristic

SPECIFICATIONS

Appearance and odor:	Clear solution with low solvent odor
Elongation:	400%
Flash point:	105 F
Percent Solids:	15% minimum
Initial cure:	1 hour
Final cure:	24 hours

SAFETY

Keep out of the reach of children! If swallowed, do not induce vomiting. Get medical attention immediately. In case of excessive skin contact, wash with soap and water. In case of eye contact, flush with water for 15 minutes and get medical attention.



Harvard Chemical Research, Inc.

Research • Development • Manufacturer