



## **Onyx Topcoat**

### **DESCRIPTION**

Onyx is a waterborne acrylic lacquer-type sealer that delivers high gloss, excellent adhesion, and protection to colored plank and cushioned tiles commonly found in the federal postal environment. Onyx demonstrates superior water resistance and dust reduction by forming a smooth, durable topcoat. This premium formulation has been developed as an un-strippable sealer that has been pigmented black to mask tile joints and scratches on the surface of plank tiles. Onyx is essential for the maintenance of interior industrial flooring where a durable, permanent finish is required

### **INSTRUCTIONS**

For best results, apply in temperatures above 40 degrees F. Surface should be free of dust, loose particles, grease, oil, and other foreign matter. Floor may be damp but not wet at application. Stir thoroughly before each use. Apply this Ready To Use product with a lambs wool applicator or rayon mop. Subsequent coats may be applied after a 24-hour cure period at a right angle to the first coat.

### **FEATURES**

- Specifically designed for black plank tiles and cushioned flooring
- Masks tile joints and scratches on surface of tiles
- Ready To Use, Easy to Apply
- Delivers a durable, permanent seal
- Coverage: 300-500 sq. ft. per gallon

### **SPECIFICATIONS**

Appearance:	Black Liquid	pH:	8.6
Odor:	Solvent	Biodegradable:	Yes
Specific gravity:	1.07	Durability:	Excellent

### **SAFETY**

For industrial use only. Use in a well ventilated area. Non-flammable at room temperature, but should be kept away from heat and fire hazards. Keep out of reach of children. Eye contact: Flush eyes with large amounts of water for at least 15 minutes. Swallowed: Give two glasses of water, call physician.