



SILTEX 444

DESCRIPTION

Siltex -444 is a state of art **Fluro-Silicon** resin blend where both *water and oil* repellency is desired. It is designed for use on marble, granite, quarry tile, limestone and unglazed porcelain tile. It will repel water, oil and will resist to staining and graffiti penetration.

Specific applications of this product are:

Sealing polished counter top stones, such as granite, marble and limestone.... to protect the stone from staining.

Red quarry tiles in kitchen and food industry, in order to repel fat, grease and water.

INSTRUCTIONS

1. Do not over apply, apply on soft white cloth and wipe onto surface. On porous surface allow product penetrate deeply and apply second time. On polished surface apply sparingly, wait and buff off any residue with soft cloth. Product may be sprayed on porous and textured surface by experienced person.

Recommended Coverage

| | |
|------------------------------------|---------------------------|
| Sandstone: | 80 - 120 sq. ft. 1 gallon |
| Granite (Polished and unpolished): | 1000 sq. ft 1 gallon |
| Limestone: | 350 - 500 sq. ft 1 gallon |
| Marble (polished and unpolished): | 1000 sq. ft. 1 gallon |
| Quarry tile: | 50 – 700 ft./ gallon |

FEATURES

- Breathable
- Oil and water repellency
- Resistant to mildew and fungus growth
- Excellent penetration

SPECIFICATIONS

| | | | |
|-------------|--------------|--------------|-------|
| Appearance: | Clear Liquid | Flash Point: | 105 F |
| Odor | Solvent | | |

SAFETY

Keep this and all chemicals out of the reach of children! This product is non-toxic to users, and non-corrosive to metal, at any dilution. It is non-flammable as well and has no flash point.