



## **TRUCK & PANEL WASH**

### **DESCRIPTION**

A high quality panel cleaner for painted trailers used as over the road vehicles. Removes heavy road film and carbon stack stains. Brushing may be necessary but usually is minimal. Do not use on anodized aluminum. Do not use on surfaces protected by new poly sealers. Sealing compound could be damaged or removed. To use for light to medium build-up use product at 4 to 6 ounces per gallon of water. For heavy buildup use at the rate of 8 ounces per gallon of water.

### **INSTRUCTIONS**

Can be applied with pressure sprayer or pressure washer used at the above dilutions. In either situation it is recommended that any application of this product to be done from the bottom of panel toward the top. If over used and applied in the wrong manner some streaking might occur. These dilutions are offered as normal use levels. In some cases a higher concentration may be necessary but care should be taken to try dilution. Test material in an inconspicuous area to guard against fading.

### **FEATURES**

- Economical - super concentrated: dilutes 200-1
- Nonflammable
- Safe on most metals, and on surfaces not harmed by water
- Works well in hard or soft water
- Biodegradable
- Cuts grease, grime, carbon, and stack stains
- Cuts heavy road film with ease
- Agitation held to a minimum

### **SPECIFICATIONS**

Appearance:	Brown Liquid	pH:	12.5-13.00
Odor:	Bland	Flammability:	None
Specific gravity:	1.06	Detergency:	Good

### **SAFETY**

Keep this and all chemicals out of the reach of children! This product is for commercial, institutional and industrial use only. Users should take care to avoid skin contact when using full strength and not allow product to splash into eyes. For skin or eye contact, flush area well with clear water for 15 minutes. In case of eye contact seek medical attention promptly. Always wash hands completely after use of product. Care should be taken to test prior to using for safest results. Do not allow this product to dry on glass, plastic or soft metals to prevent possible etching or pitting. Rinse these surfaces thoroughly after use.