



## **X-PELL SS**

### **DESCRIPTION**

X-PELL SS is a oligomeric Silane/Siloxane blend resin; the extremely small molecular structure of the sealer permits maximum penetration into the mineral substrate to achieve water repellency.

X-PELL SS is extremely effective on architectural concrete, exposed aggregate, brick, mortar, natural stones, including marble, granite, and sandstone. Testing is recommended before applying to determine if any darkening will occur.

### **INSTRUCTIONS**

1. Apply by low-pressure sprayer or by roller
2. On vertical surfaces, soak the surface until excess runs down 6 to 8 inches below the spray pattern. On horizontal surfaces, apply by flooding until saturation is achieved, but avoid puddling or ponding.

### **Recommended Coverage**

Concrete:	100 - 200 sq. ft 1 gallon
Sandstone:	80 - 120 sq. ft. 1 gallon
Granite:	500 - 700 sq. ft 1 gallon
Limestone:	80 - 120 sq. ft 1 gallon
Marble:	500 - 700 sq. ft. 1 gallon

### **FEATURES**

- Good alkali resistance
- Breathable
- Resistant to mildew and fungus growth
- Excellent penetration
- Low VOC
- Improves coating adhesion

### **SPECIFICATIONS**

Appearance:	Clear liquid	pH:	NA Solvent
Solvents:	None	Detergency:	Excellent
Odor:	Mild	Flammable:	No
Specific gravity:	.823		

### **SAFETY**

Keep out of the reach of children! If swallowed, do not induce vomiting. Get medical attention immediately. In case of excessive skin contact, wash with soap and water. In case of eye contact, flush with water for 15 minutes and get medical attention.